

ET MAC-200-31DS

AUTOMATIC BATTERY CHARGERS FOR WET BATTERIES REV 0602

Data Sheet REPLACES 0102

# OF CELLS	MAC MODEL NUMBER	DC AMPS	120V AC AMPS	AH RECHARGE CAPACITY 8HR - 16HR	CASE	APPROXIMATE SHIP WEIGHT LBS. KG.	
6 12 VOLT	*ET121016	10	1.8	54 - 108	S3	20	9.08
	*ET121516	15	2.7	80 - 160	T3	23	10.44
	*ET122016	20	3.6	107 - 214	T3	26	11.79
	*ET123016	30	5.4	161 - 322	T3	29	13.16
	*ET124016	40	7.2	214 - 428	P3	33	14.98
	*ET125016	50	9.0	268 - 536	P3	37	16.79
12 24 VOLT	ET241016	10	3.6	54 - 108	S3	21	9.53
	ET241516	15	5.4	80 - 160	T3	24	10.89
	ET242016	20	7.0	107 - 214	T3	30	13.62
	ET242516	25	9.0	134 - 268	T3	32	14.52
	ET243016	30	10.8	161 - 322	T3	37	16.78
	ET244016	40	14.4	214 - 428	P3	54	24.49
18 36 VOLT	ET361016	10	5.4	54 - 108	S3	22	9.98
	ET361516	15	8.1	80 - 160	T3	26	11.79
	ET362016	20	10.8	107 - 214	T3	34	15.43
	ET362116	21	11.3	113 - 225	T3	35	15.89
	ET362516	25	13.3	134 - 268	T3	39	17.69
	ET363016	30	14.8	161 - 322	T3	58	26.30
24 48 VOLT	ET481016	10	7.2	54 - 108	T3	35	15.89
	ET481716	17	12.2	91 - 182	T3	40	18.14
	ET482016	20	14.4	107 - 214	T3	49	22.22

ABOVE CHARGERS MUST SHIP WITH DC PLUGS

MECHANICAL

ELECTRICAL

Case = S3	Case = T3	Case = P3	Input -	Output -
Height = 7.9"	Height = 10.6"	Height = 12.4"	120 Volt ± 10%	Voltage
Width = 9.0"	Width = 8.4"	Width = 9.4"	1 Phase, 60 HZ	Regulation ± 1%
Depth = 6.4"	Depth = 10.6"	Depth = 14.5"	Power cord 8ft.	at finish rate charge.
			Contact MAC for other voltage and frequency inputs not shown.	Power cord 7ft.

(Height with handle)



*except